ZINC PRIME® GALVANIZE – PRODUCT CATALOG

Product Description
A high-solids, rust-inhibitive alkyd primer designed for interior and exterior use on ferrous and non-ferrous metals, including galvanized steel and aluminium. Provides excellent adhesion and weather resistance.

Intended Uses
• Structural steel
• Tank exteriors
• Pipes and industrial equipment
• Shop primer applications

Key Features
• Suitable for galvanized and ferrous metals
• Excellent corrosion resistance
• Fast drying
• High solids
• Lead and chromate-free formulation

Technical Data
• Volume Solids: 62% ± 2%
• Dry Film Thickness: 50–63 microns
• Theoretical Coverage: 10.88 m²/litre
• Drying Time at 25°C: Touch dry 15 min, Hard dry 60 min

Surface Preparation
Surfaces must be clean, dry, and free of contaminants. Follow ISO 8504 guidelines. Galvanized surfaces should be degreased and cleaned before priming.

Application Methods
• Airless spray
• Roller
• Brush
Thinner: T-5 Thinner

Safety Information
Use only in well-ventilated industrial environments. Refer to the MSDS before handling. Avoid inhalation of fumes and ensure proper protective equipment.

Storage
Minimum 12 months at 25°C. Store in dry, shaded areas away from heat sources.